

filtros de malla en Y - GAMA PROFESIONAL

Y conical mesh filters-professional range / gamme professionnelle-filtres de mailles en Y



punto pieza.
color of spot on item
pastille de couleur sur pièce

	Ø	L/H(1)			€	€	(p. 54) repuesto malla mesh spares rechanges filtres
• REF. 1411	3/4" - 50 MESH	4.800	C	30	7,17	215,10	REF. 1470
• REF. 1410	3/4" - 100 MESH	4.800	C	30	7,17	215,10	REF. 1471
• REF. 1413	3/4" - 120 MESH	4.800	C	30	7,17	215,10	REF. 1472
• REF. 1421	1" - 50 MESH	6.600	C	15	9,95	149,25	REF. 1476
• REF. 1420	1" - 100 MESH	6.600	C	15	9,95	149,25	REF. 1477
• REF. 1423	1" - 120 MESH	6.600	C	15	9,95	149,25	REF. 1478
• REF. 1427	1.1/4" - 50 MESH	9.900	C	10	11,44	114,40	REF. 1465
• REF. 1428	1.1/4" - 100 MESH	9.900	C	10	11,44	114,40	REF. 1466
• REF. 1429	1.1/4" - 120 MESH	9.900	C	10	11,44	114,40	REF. 1467
• REF. 1441	1.1/2" - 50 MESH	10.500	D	10	16,98	169,80	REF. 1479
• REF. 1440	1.1/2" - 100 MESH	10.500	D	10	16,98	169,80	REF. 1480
• REF. 1443	1.1/2" - 120 MESH	10.500	D	10	16,98	169,80	REF. 1481
• REF. 1446	2" - 50 MESH	18.000	D	5	29,70	148,50	REF. 1486
• REF. 1445	2" - 100 MESH	18.000	D	5	29,70	148,50	REF. 1485
• REF. 1448	2" - 120 MESH	18.000	D	5	29,70	148,50	REF. 1487

(1) pérdidas de carga 0,2 bar con malla de 100 MESH
0,2 bar of pressure loss with 100 Mesh grade filter
Perte de Charge de 0,2 bar avec une maille de 100 Mesh

Se fabrica bajo pedido: Rosca NPT en Filtros de 1" - 1.1/2" y 2"

NPT thread for 1", 1.1/2" and 2" filters upon orders

Sur commande: filet NPT pour les filtres de 1" - 1.1/2" et 2"


pérdidas de carga (bar) en función del caudal con malla de 100 MESH
pressure loss (bar) as a function of flow with a grade 100 MESH
pertes de charges (bar) en fonction du débit avec maille de 100 MESH

	Q (l/min.)									
	40	80	120	160	200	250	300	350	400	500
3/4"	0,05	0,20	0,43	0,72						
1"	0,04	0,12	0,23	0,37	0,62					
1. 1/4"	0,02	0,05	0,10	0,18	0,34	0,56				
1. 1/2"	0,02	0,05	0,09	0,16	0,30	0,50				
2"			0,03	0,06	0,09	0,14	0,19	0,25	0,32	0,45

presión de trabajo máxima
maximum operating pressure
pression de travail maximale

3/4"	1"	1.1/4"	1.1/2"	2"
12 bar		10 bar		8 bar

	50 MESH	100 MESH	120 MESH
punto pieza item point pastille			



se pueden suministrar como piezas sueltas / can be supplied as loose items / ils peuvent être fournis en pièces détachées

filtros de malla en Y - GAMA "S"

Y conical mesh filters - "S" RANGE / GAMME "S" - filtres de mailles en Y



punto pieza.
color of spot on item
pastille de couleur sur pièce



Gama "S"
"S" range
Gamme "S"

	Ø	L/H(1)			€	€	(p. 54) repuesto malla mesh spares rechanges filtres
• REF. 1404	1/2" S - 50 MESH	4.500	B	20	4,68	93,60	REF. 1460
• REF. 1405	1/2" S - 100 MESH	4.500	B	20	4,68	93,60	REF. 1461
• REF. 1406	1/2" S - 120 MESH	4.500	B	20	4,68	93,60	REF. 1462
• REF. 1407	3/4" S - 50 MESH	4.500	B	20	4,68	93,60	REF. 1460
• REF. 1408	3/4" S - 100 MESH	4.500	B	20	4,68	93,60	REF. 1461
• REF. 1409	3/4" S - 120 MESH	4.500	B	20	4,68	93,60	REF. 1462
• REF. 1415	1" S - 50 MESH	4.800	C	30	7,17	215,10	REF. 1470
• REF. 1416	1" S - 100 MESH	4.800	C	30	7,17	215,10	REF. 1471
• REF. 1417	1" S - 120 MESH	4.800	C	30	7,17	215,10	REF. 1472
• REF. 1424	1.1/4" S - 50 MESH	6.600	C	15	9,95	149,25	REF. 1476
• REF. 1425	1.1/4" S - 100 MESH	6.600	C	15	9,95	149,25	REF. 1477
• REF. 1426	1.1/4" S - 120 MESH	6.600	C	15	9,95	149,25	REF. 1478
• REF. 1435	1.1/2" S - 50 MESH	9.900	C	10	11,44	114,40	REF. 1465
• REF. 1436	1.1/2" S - 100 MESH	9.900	C	10	11,44	114,40	REF. 1466
• REF. 1437	1.1/2" S - 120 MESH	9.900	C	10	11,44	114,40	REF. 1467
• REF. 1449	2" S - 50 MESH	10.500	D	10	16,98	169,80	REF. 1479
• REF. 1450	2" S - 100 MESH	10.500	D	10	16,98	169,80	REF. 1480
• REF. 1451	2" S - 120 MESH	10.500	D	10	16,98	169,80	REF. 1481
• REF. 1452	2.1/2" S - 50 MESH	18.000	D	5	29,70	148,50	REF. 1486
• REF. 1453	2.1/2" S - 100 MESH	18.000	D	5	29,70	148,50	REF. 1485
• REF. 1454	2.1/2" S - 120 MESH	18.000	D	5	29,70	148,50	REF. 1487

(1) pérdidas de carga 0,2 bar con malla de 100 MESH
0,2 bar of pressure loss with 100 Mesh grade filter
Perte de Charge de 0,2 bar avec une maille de 100 Mesh

pérdidas de carga (bar) en función del caudal con malla de 100 MESH
pressure loss (bar) as a function of flow with a grade 100 MESH
peries de charges (bar) en fonction du débit avec maille de 100 MESH

	Q (l/min.)									
	40	80	120	160	200	250	300	350	400	500
1/2" y 3/4"	0,05	0,23	0,49	0,79						
1"	0,05	0,20	0,43	0,72						
1.1/4"	0,04	0,12	0,23	0,37	0,62					
1. 1/2"	0,02	0,05	0,10	0,18	0,34	0,56				
2"	0,02	0,05	0,09	0,16	0,30	0,50				
2.1/2"			0,03	0,06	0,09	0,14	0,19	0,25	0,32	0,45

presión de trabajo máxima
maximum operating pressure
pression de travail maximale

							50 MESH	100 MESH	120 MESH
1/2"	3/4"	1"	1.1/4"	1.1/2"	2"	2.1/2"			
12 bar									
10 bar									
8 bar									

punto pieza
item point
pastille